

| | | | Design | Data Sheet | | | |
|-------------------|-------------------|-------------------|-----------------|---------------------------------------|------------------------|------------------|--------|
| | Design Parameters | (Metric) | | Design | Parameters (US Standar | rd) | |
| | | Vessel | Jacket | | | Vessel | Jacket |
| sure (MPa) | | 0.1 | 0.1 | Working Pressure (psi) | | 14.5 | 14.5 |
| re (MPa) | | 0.2 | 0.4 | Design Pressure (psi) | | 29 | 58 |
| p (°C) | | -5 - 40 | | Working Temp (°F) | | 23 - 104 | |
| (°C) | | -10 - 50 | | Design Temp (°F) | | 14 - 122 | |
| | | Beer | Glycol | | | Beer | Glycol |
| | | 304 | 304 | Material | | 304 | 304 |
| (gal) | | 1537.6 (49.6BBL) | | Gross Voume (gal) | | 1537.6 (49.6BBL) | |
| gal) | | 1240 (40BBL) | 25 | Net Volume (gal) | | 1240 (40BBL) | 25 |
| ct Pressure (MPa) | | 0.1 | | Saftey Valve Act Pressure (psi) | | 14.5 | |
| e Area (m²) | | 8.8 | | Heat Exchange Area (ft ²) | | 95.2 | |
| terial | | | | Insulation Material | | PU | |
| ckness (mm) | | 80 | | Insulation Thickness (in) | | 3.2 | |
| (MPa) | | 0.2 | 0.6 | Pressure Test (psi) | | 29 | 87 |
| | | | | | | | |
| | | | | nensions | | | |
| Name | Connect Size (mm) | Connect Size (in) | Connect Type | Comments | | (mm) | (in) |
| Manhole | 580x480 | 22.9x18.9 | | | Total Height | 3880 | 152.8 |
| CO2 Inlet | 38.1 | 1.5 | Clamp | | Minimum Height | 3738 | 147.2 |
| essure Gauge | 38.1 | 1.5 | Clamp | | Total Diameter | 2161 | 85 |
| Assembly Clamp | 38.1 | 1.5 | Clamp | 2 clamps | Tank Diameter | 1960 | 77.2 |
| Converter Clamp | 101.6 | 4 | Clamp | | Ceiling Clearance | 3847 | 151.5 |
| Spray Ball Clamp | 38.1 | 1.5 | Clamp | | Shipping Clearance | | |
| Beer Out | 38.1 | 1.5 | Clamp | 2 clamps | | | |
| Yeast Out | 50.8 | 2 | Clamp | 3 clamps, includes reducer to 1.5" | Gasket Count | | |
| Temp Gauge | 38.1 | 1.5 | Clamp | | 1.5" | 13 | |
| Saftey Valve | 50.8 | 2 | Clamp | | 2" | 4 | |
| Hop Port | 152.4 | 6 | Clamp | | 4" | 1 | |
| Sample Valve | 38.1 | 1.5 | Clamp | | 6" | 1 | |
| rmocouple Port | | NPT ½" | Female Threaded | | | | |
| Overflow | 38.1 | 1.5 | Clamp | 3 clamps | | kg | lbs |
| Glycol In | | NPT 1" | Female Threaded | | Weight | 940 | 2072.4 |
| Glycol Out | | NPT 1" | Female Threaded | | | | |