

			Design Data Sheet			
Design Par	ameters (Metric)		Design Parameters (US Standard)			
	Vessel	Jacket		Vessel	Jacket	
Working Pressure (MPa)	0.1	0.1	Working Pressure (psi)	14.5	14.5	
Design Pressure (MPa)	0.2	0.4	Design Pressure (psi)	29	58	
Working Temp (°C)	-5 -	40	Working Temp (°F)	23 - 104		
Design Temp (°C)	-10 -	50	Design Temp (°F)	14 - 122		
Material	304	4	Material	304		
Gross Voume (gal)	3053.5 (98.5BBL)		Gross Voume (gal)	3053.5 (98.5BBL)		
Net Volume (gal)	2480 (80BBL)	41	Net Volume (gal)	2480 (80BBL)	41	
Head Space	239	%	Head Space	23%		
Saftey Valve Act Pressure (MPa)	0.1	l	Saftey Valve Act Pressure (psi)	14.5	14.5	
Heat Exchange Area (m²)	15.	5	Heat Exchange Area (ft²)	166.9	166.9	
Insulation Material	PU	J	Insulation Material	PU	PU	
Insulation Thickness (mm)	80)	Insulation Thickness (in)	3.2		
Pressure Test (MPa)	0.2	2	Pressure Test (psi)	29		

Component Specifications						Dimensions		
	Name	Connect Size (mm)	Connect Size (in)	Connect Type	Comments		(mm)	(in)
a	Manhole	580x480	22.9x18.9			Total Height	4195	165.1
b	CO2 Inlet	38.1	1.5	Clamp		Minimum Height	4058	159.8
c1	Outlet	152.4	6	Clamp		Total Diameter	2467	97.1
c2	Drain Outlet	50.8	2	Clamp	2 Clamps, includes reducer to 1.5"	Tank Diameter	2264	89.1
c3	Beer Outlet	38.1	1.5	Clamp	2 Clamps	Shipping Clearance	4160	163.8
d	Pressure Gauge	38.1	1.5	Clamp				
e	Thermocouple Port		NPT ½"	Female Threaded				
f	Temp Gauge	38.1	1.5	Clamp		Gasket Count		
g	Sample Valve	38.1	1.5	Clamp		1.5"	11	
h1-3	CIP Assembly Clamps	38.1	1.5	Clamp	3 clamps	2"	3	
h4	CIP Converter Clamp	101.6	4	Clamp		4"	1	
h5	CIP Spray Ball	38.1	1.5	Clamp		6"	1	
i1-2	Level Ports	19	3/4	Clamp	3 Clamps. Hose runs between ports (not included)			
j	Safety Valve	50.8	2	Clamp			kg	lbs
m1-3	Glycol In		NPT 1"	Female Threaded		Weight	1560	3439.3
m4-6	Glycol Out		NPT 1"	Female Threaded				



MFG APPR.

SIZE TITLE: REV A

SHEET 1 OF 1

SCALE: 1:25

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ABS COMMERCIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ABS COMMERCIAL IS PROHIBITED.