


Design Parameters (Metric)		Design Parameters (US Standard)	
Working Pressure (MPa)	0.1	Working Pressure (psi)	14.5
Design Pressure (MPa)	0.2	Design Pressure (psi)	29
Working Temp (°C)	-5 - 40	Working Temp (°F)	23 - 104
Design Temp (°C)	-10 - 50	Design Temp (°F)	14 - 122
Material	304	Material	304
Gross Voume (gal)	399.9 (12.9BBL)	Gross Voume (gal)	399.9 (12.9BBL)
Net Volume (gal)	310 (10BBL)	Net Volume (gal)	310 (10BBL)
Head Space	29%	Head Space	29%
Saftey Valve Act Pressure (MPa)	0.1	Saftey Valve Act Pressure (psi)	14.5
Pressure Test (MPa)	0.2	Pressure Test (psi)	29

Dimensions								
	Name	Connect Size (mm)	Connect Size (in)	Connect Type	Comments		(mm)	(in)
a	Manhole	580x480	22.9x18.9			Total Height	2079	81.8
b	CO2 Inlet	38.1	1.5	Clamp		Minimum Height	1942	76.4
c	Outlet	50.8	2	Clamp	3 Clamps, includes reducer to 1.5"	Total Diameter	1415	55.7
d	Pressure Gauge	38.1	1.5	Clamp		Tank Diameter	1208	47.6
f	Temp Gauge	38.1	1.5	Clamp				
g	Sample Valve	38.1	1.5	Clamp		Gasket Count		
h1-3	CIP Assembly Clamps	38.1	1.5	Clamp	3 clamps	1.5"	9	
h4	CIP Converter Clamp	101.6	4	Clamp		2"	4	
h5	CIP Spray Ball	38.1	1.5	Clamp		4"	1	
i1-2	Level Ports	19	3/4	Clamp	3 Clamps. Hose runs between ports (not included)			
j	Safety Valve	50.8	2	Clamp				
						Weight	kg	lbs
							240	529.1



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
ABS COMMERCIAL. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
ABS COMMERCIAL IS  
PROHIBITED.

	NAME	DATE
DRAWN	MJM	2/13/2023
CHECKED	MWM	2/13/2023
ENG APPR.		
MFG APPR.		

COMMENTS:

ABS COMMERCIAL		
ABS COMMERCIAL		
SIZE A	TITLE: 010SER0A	REV A
SCALE: 1:14		SHEET 1 OF 1