



Design Paramete	ers (Metric)	Design Parameters (US Standard)		
Working Pressure (MPa)	0.1	Working Pressure (psi)	14.5	
Design Pressure (MPa)	0.2	Design Pressure (psi)	29	
Working Temp (°C)	-5 - 40	Working Temp (°F)	23 - 104	
Design Temp (°C)	-10 - 50	Design Temp (°F)	14 - 122	
Material	304	Material	304	
Gross Voume (gal)	558 (18BBL)	Gross Voume (gal)	558 (18BBL)	
Net Volume (gal)	465 (15BBL)	Net Volume (gal)	465 (15BBL)	
Head Space	20%	Head Space	20%	
Saftey Valve Act Pressure (MPa)	0.1	Saftey Valve Act Pressure (psi)	14.5	
Pressure Test (MPa)	0.2	Pressure Test (psi)	29	

					Dimensions			
	Name	Connect Size (mm)	Connect Size (in)	Connect Type	Comments		(mm)	(in)
а	Manhole	580x480	22.9x18.9			Total Height	2243	88.3
b	CO2 Inlet	38.1	1.5	Clamp		Minimum Height	2106	82.9
С	Outlet	50.8	2	Clamp	3 Clamps, includes reducer to 1.5"	Total Diameter	1504	59.2
d	Pressure Gauge	38.1	1.5	Clamp		Tank Diameter	1307	51.4
f	Temp Gauge	38.1	1.5	Clamp				
g	Sample Valve	38.1	1.5	Clamp		Gasket Count		
h1-3	CIP Assembly Clamps	38.1	1.5	Clamp	3 clamps	1.5"	9	
h4	CIP Converter Clamp	101.6	4	Clamp		2"	4	
h5	CIP Spray Ball	38.1	1.5	Clamp		4"	1	
i1-2	Level Ports	19	3/4	Clamp	3 Clamps. Hose runs between ports (not included)			
j	Safety Valve	50.8	2	Clamp			kg	lbs
						Weight	345	760.6





NAME

MJM

DRAWN CHECKED

ENG APPR.

MFG APPR.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ABS COMMERCIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ABS COMMERCIAL IS PROHIBITED.

DATE

2/13/2023

COMMERCIAL

SCALE: 1:16

SIZE TITLE: O15SEROA A

SHEET 1 OF 1